



SECTION I	PRODUCT AND COMPANY IDENTIFICATION							
TRADE NAME:	Hydrofluosilicic Acid							
CHEMICAL NAME:	Hydrofluosilicic Acid							
CAS NUMBER:	16961 - 83 – 4							
CHEMICAL FAMILY:	Inorganic Fluorides							
SYNONYMS:	Fluorosilicic Acid Hexafluosilicic Acid HFS FSA							
PRIMARY USE:	Industrial Chemical							
COMPANY INFORMATION:	Mosaic Crop Nutrition, LLC 13830 Circa Crossing Drive Lithia, Florida 33547 www.mosaicco.com 866-928-7901 or 306-523-2800, 8 AM to 5 PM Central Time US							
EMERGENCY TELEPHONE:	CHEMTREC 1-800-424-9300							
SECTION II	HAZARD IDENTIFICATION							
EMERGENCY OVERVIEW:	Health Hazards: Corrosive to the skin, eyes and mucous membranes through direct contact, inhalation ingestion. May cause severe irritation and burns, which may not be immediately appared Handle with extreme care.				halation or and			
	Physical Hazards	S:		Not appl	icable	ole		
	Physical Form: Appearance: Water white to amber liquid							
				liquid				
	Odor: Pungent							
	NFPA HAZARI CLASS	D	HMIS HAZAF				WHMIS HAZA CLASS	RD
ı	Health:	3	Hea		3		Symbol	
	Flammability:	0		nmability:	0	L		
	Instability:	1		sical ard:	0	-	Classification	E
	Special Hazard:	Corrosive	PPI	<u>:</u>	Section 8	L	Sub Class	
POTENTIAL HEALTH EFFECTS:	irritation, damage Skin: Corrosiv			ve. Contact may cause severe n, eye burns, and permanent eye e. ve. Contact may cause severe n, skin burns, and permanent skin				
	Inhalation (Breathing)			damage. Corrosive. Harmful if inhaled. May cause severe irritation and burns of the nose, throat, and respiratory tract.				





		ANSI/NSF 60		
	Ingestion (Swallowing)	Corrosive. Harmful or fatal if swallowed. May		
		cause severe irritation and burns of the mouth,		
		throat and digestive tract.		
	Signs and Symptoms:	Effects of overexposure may include severe		
		irritation and burns of the mouth, nose, throat,		
		respiratory and digestive tract. Symptoms of		
		overexposure may include ulceration of the		
		nose and throat, coughing, salivation,		
		headache, fatigue, dizziness, nausea, shock,		
		and pulmonary edema (accumulation of fluid		
		around the lungs). May lead to coma or death.		
		Onset of symptoms may be delayed.		
	Cancer:	The ingredient(s) of this product is (are) not		
		classified as carcinogenic by NTP, IARC, or OSHA		
	Target Organs:	No data available for this material (see Other Comments below).		
	Developmental:	No data available for this material		
	Other Comments:	Prolonged or repeated overexposure to fluoride		
		compounds may cause fluorosis. Fluorosis is		
		characterized by skeletal changes, consisting		
		of osteosclerosis (hardening or abnormal		
		density of bone) and osteomalacia (softening of		
		bones) and by mottled discoloration of the		
		enamel of teeth (if exposure occurs during		
		enamel formation). Symptoms may include		
		bone and joint pain and limited range of		
		motion. Conditions aggravated by exposure		
		may include skin and respiratory (asthma-like)		
		disorders.		
	Pre-Existing Medical	Conditions aggravated by exposure may		
	Conditions:	include skin and respiratory (asthma-like)		
		disorders.		
POTENTIAL				
ENVIRONMENTAL EFFECTS:				
SECTION III	COMPOSITION / IN	FORMATION ON INGREDIENTS		
FORMULA:	H ₂ SiF ₆			
COMPOSITION:	Hydrofluosilicic Acid	20-25%		
	Fluoride	19%		
	Water	75-80%		
SECTION IV	FIRST AID MEASURES			
FIDOT AID	Eyes:	Immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately.		
FIRST AID PROCEDURES:	Skin:	Immediately flush with plenty of water. Remove contaminated clothing. Discard contaminated clothing properly. Get medical attention if irritation occurs or persists.		





	*	ANSI/NSF 60		
	Inhaled:	Move to fresh air. Administer oxygen. Treat symptomatically. Get medical attention promptly. Observe for possible delayed reaction.		
	Ingestion:	Do Not induce vomiting. Give large quantities of milk or water to patient if conscious. Seek medical attention promptly.		
NOTE TO PHYSICIAN:				
SECTION V	FIRE FIGHTING MEASURES			
	Flash Point:	Not applicable		
	OSHA Flammability Class:	Not applicable		
Flammable Properties:	LEL/UEL:	Not applicable		
	Auto-Ignition Temperature:	Not applicable		
Extinguishing Media:	Small fires: Water spray, foam, dry chemical or CO ₂ . Large fires: Water spray, fog or foam.			
	Wear self-contained breathing apparatus with full protective clothing.			
Protection of Firefighters:	Fluorosilicic Acid is not flammable, however when heated to decomposition, highly toxic and corrosive fumes of fluorides are emitted. May generate flammable and explosive hydrogen gas in contact with some metals.			
SECTION VI	ACCIDENTAL RELEASE MEASURES			
RESPONSE TECHNIQUES:	Small spills: Contain spill and stop leak if it can be done without risk. Neutralize acid spill using sodium carbonate or a mixture of soda ash and slaked lime. Absorb material with sand o vermiculite or inert absorbent material. Place in DOT-approved poly container and dispose of properly.			
	Large spills: Isolate spill area and deny entry. Prevent discharge into waterways and sewers. If possible transfer material to appropriate containers for reclamation or disposal. Remaining spill may be neutralized with sodium carbonate or a mixture of soda ash and slaked lime. Contact proper local, state, or federal regulatory agencies to ascertain proper disposal techniques and procedures. All waste to be collected in a DOT-approved poly drum for disposal.			
SECTION VII	HANDLING AND STORAGE			
HANDLING:	Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Maintain proper hygiene practices when handling this product.			
STORAGE:	Store in tightly closed containers, in a well ventilated area. Keep away from heat, combustible materials, strong bases and metals. Large storage tanks should be bermed. Avoid using glass, metal or ceramic containers.			
SECTION VIII	EXPOSURE CONTROLS / PERSONAL PROTECTION			
ENGINEERING CONTROLS:	Assure that ventilation is adequate to control airborne levels.			
PERSONAL	Eye/Face: Splash proof goggles and full-face shield should be worn at all times.			





EQUIPMENT (PPE):	Skin:	Acid proof gloves, headgear, protective shoes and clothing should be worn to prevent contact.		
	Respiratory:	Wear NIOSH approved respiratory protective equipment when vapor or mists may exceed applicable concentration limits.		
	Other:	Facilities utilizing or storing this material should be equipped with an eyewash station and a safety shower.		
GENERAL HYGIENE CONSIDERATIONS:	Avoid breathing fumes. Avoid ingestion Wash thoroughly after handling Avoid contact with eyes or skin Use with adequate ventilation			
EXPOSURE GUIDELINES:	OSHA Permissible Exposure Limits (PEL):	2.5 mg/m ³ as Fluoride		
	ACGIH Threshold Limit Value (TLV): TLV-TWA	2.5 mg/m ³ as Fluoride		
	BIOLOGICAL EXPOSURE INDEX (BEI) Index Timing BEI Fluoride in urine Prior to shift 3 mg/L; End of shift 10 mg/L ACGIH 2004			
SECTION IX	PHYSICAL ANI	D CHEMICAL PROPERTIES		
Note: Unless otherwise state	d, values in this section are determined at 20	°C (68°F) and 760 mm Hg (1 atm).		
Flash Point:	Not applicable			
Flammability/Explosive Limits (%):	Not applicable			
Auto-Ignition Temperature:	Not applicable			
Appearance:	Water white to amber liquid			
Physical State:	Liquid			
Odor:	Pungent			
Molecular Weight of Pure Material:	144.11			
	144.11			
Pure Material:				
Pure Material: pH: Vapor Pressure(mm	1.2			
Pure Material: pH: Vapor Pressure(mm Hg):	1.2 Not applicable			
Pure Material: pH: Vapor Pressure(mm Hg): Vapor Density(air=1):	1.2 Not applicable Not applicable			
Pure Material: pH: Vapor Pressure(mm Hg): Vapor Density(air=1): Boiling Point: Freezing/Melting	1.2 Not applicable Not applicable 222 – 223 °F			
Pure Material: pH: Vapor Pressure(mm Hg): Vapor Density(air=1): Boiling Point: Freezing/Melting Point:	1.2 Not applicable Not applicable 222 – 223 °F Not applicable			





	ANSINSF 60			
Bulk Density:	9.7 – 10.1 lb/gallon at 25% Sol. @ 77°F			
SECTION X	STABILITY AND REACTIVITY			
Chemical Stability:	Stable under recommended conditions of storage, handling and proper use.			
Conditions to Avoid:	Avoid all heat sources.			
Incompatible Materials:	Avoid contact with metals, stoneware, strong acids and alkalies, explosives, toxicants, readily oxidizable materials, alkali metals, combustible solids, and organic peroxides.			
Hazardous Decomposition Products:	Extreme temperatures such as a fire cause formation of highly toxic and corrosive fumes of fluorides such as SiF ₄ and HF. Hydrogen gas may be formed at temperatures above 227°F.			
Corrosiveness:	Attacks silica bearing materials, metals, and stoneware			
Hazardous Polymerization:	Will not occur.			
SECTION XI	TOXICOLOGICAL INFORMATION			
Acute Oral Toxicity	LD50 = 200 mg/Kg (guinea pig)			
Acute Inhalation Toxicity	LC50 850 – 1070 ppm / 1 hour (Rat)			
Acute Dermal Toxicity	140 mg/kg LDLo (Frog)			
Mutagenesis	No data available			
Target Organ	No data available			
Developmental Toxicity	No data available			
Carcinogenicity	No data available			
SECTION XII	ECOLOGICAL INFORMATION			
Ecotoxicology	No data available			
SECTION XIII	DISPOSAL CONSIDERATIONS			
	This material, if discarded in the same state as it was delivered, meets RCRA Hazardous Waste characteristic for Corrosivity (D002) See 40CFR261.22. Keep in covered DOT-approved container pending disposal. Handle and dispose in full compliance with all applicable International, Federal, State and Local regulations.			
SECTION XIV	TRANSPORT INFO			
Regulatory Status	Regulated by US DOT, Canada TDG, IATA, IMO/IMDG			
Proper Shipping Name	Fluorosilicic Acid			





	*	ANSI/NSF 60		
Hazard Class	Class 8 (Corrosive)			
Packing Group	II			
Identification Number	UN1778			
DOT ERG Number	154			
SECTION XV	REGULATORY INFORMATION			
CERCLA:	Not Regulated			
RCRA 261.33:	Not Regulated			
SARA TITLE III:	Section 302: Not Regulated			
(Exemptions at 40 CFR, Part 370 may apply for	Section 304: Not Regulated			
agricultural use, or for quantities of less than 10,000 pounds on-site.)	Section 311/312: Acute and Chronic Section 313: Not Regulated			
NTP, IARC, OSHA:	The ingredient(s) of this product is (are) not classified as carcinogenic by NTP, IARC, or OSHA			
Canada DSL and NDSL:	On Inventory			
TSCA:	On Inventory			
CA Proposition 65: (Health & Safety Code Section 25249.5)	Not listed			
WHMIS:	Fluorosilicic acid is listed as a Class E - Corrosive Material. This MSDS has been prepared according to the hazard criteria of the Controlled Product Regulations (CPR) and MSDS contains all of the information required by the CPR			
CBSA:	N/A			
SECTION XVI	OTHER INFORMATION			
Disclaimer:	The information in this document is believed to be correct as of the HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNE PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS E TO BE IMPLIED REGARDING THE ACCURACY OR COMPLE INFORMATION, THE RESULTS TO BE OBTAINED FROM THE INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PETHE HAZARDS RELATED TO ITS USE. This information and permination as to suitability of the product for their particular percondition that they assume the risk of their use thereof. The corthis product are beyond the control of Mosaic, and Mosaic disclass or damage incurred in connection with the use or misuse of	ESS FOR ANY EXPRESSED OR ETENESS OF THE IE USE OF THIS PRODUCT, OR product are make their own purpose and on the nditions and use aims any liability	che for	
Preparation:	The preparation of this MSDS was in accordance with ANSI Z40			
Note to (if applicable):				